




DFP-102MR

DIPLEXER



ELECTRICAL SPECIFICATIONS

RECEIVE CHARACTERISTICS, ANT TO REC

PASSBAND	243-270 MHz
VSWR, Ref 50 Ohms	1.5:1 max.
INSERTION LOSS	0.7 dB max.
REJECTION	
0-130 MHz	45 dB min.
130-190 MHz	35 dB min.
292-300 MHz	50 dB min.
300-450 MHz	70 dB min.

TRANSMIT CHARACTERISTICS, TRAN to ANT

PASSBAND	292-318 MHz
INSERTION LOSS, @ fo	0.5 dB max.
INSERTION LOSS, over band	0.6 dB max.
VSWR, Ref 50 Ohms	1.4:1 max.
INPUT POWER	+23 dBW max.
REJECTION	
0-270 MHz	35 dB min.
360-1000 MHz	35 dB min.

GENERAL CHARACTERISTICS

ENVIRONMENTAL	AIRBORNE
WEIGHT	2 lbs. 8 oz.
SIZE, excluding connectors	5.55" x 5.10" x 1.56"
CONNECTORS	
J1 (ANT)	TYPE N (FEMALE)
J2 (REC)	TYPE TNC (FEMALE)
J3 (TRAN)	TYPE N (FEMALE)

REV: 8/23/17